MT3A-30L-14-10K-C3 ✔ ACTIVE

MEAS | MEAS MT Mini-Test

TE Internal #: 10202493-00

TE Internal Description: MT3A-30L-14-10K-C3

MT3A Mini IP67 String Potentiometer

View on TE.com >

Sensors > Position Sensors > Potentiometer Sensors > Cable Actuated Position Sensors > MT3A Mini IP67 String Potentiometer



Position Sensor Product Type: **Miniature String Potentiometer**

Full Stroke Range: **762 mm [30 in]**

Output Signal Type: **Voltage Divider (Potentiometric)**

Accuracy: **±.15 % of FS**

Repeatability: **.02 % of FS**

All MT3A Mini IP67 String Potentiometer (72)

Features

Product Type Features

Position Sensor Product Type	Miniature String Potentiometer

Body Features

Case Material	Aluminum

Dimensions

Full Stroke Range	762 mm[30 in]

Usage Conditions

Accuracy	±.15 % of FS
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Operation/Application

Output Signal Type	Voltage Divider (Potentiometric)

Industry Standards

IP Rating	IP67

Other

Encoder Drive	No
Repeatability	.02 % of FS
Measuring Cable	.019 Inch Dia Nylon-Coated Stainless Steel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) SVHC > Threshold: Pb (3.5% in Component Part) **Article Safe Usage Statements:** Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles'(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Also in the Series | MEAS MT Mini-Test



Cable Actuated Position Sensors(241)

Documents

MT3A-30L-14-10K-C3

Datasheets & Catalog Pages

MT3A

English