Data sheet

KEBI QL 302015 S2B0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



For many years, the name Klippon® has stood for competence and quality in enclosures.
The Klippon® EBi industrial enclosure series protects your components reliably if they are used in moderate environmental conditions and is designed for everyday applications. With the ever-increasing need for individual application solutions, the Klippon® EBi with its high degree of protection and impact resistance is ideally suited to your needs.
Our standard product is the Klippon® EBi QL – with hinged door and double-bit key lock.
A variant with mounting screws is also available, but is only manufactured on request and is subject to a minimum order quantity. DNV GL and cULus approvals are also available on request.

General ordering data

Version	Klippon EBi QL (Essential Box industrial - Quarter Lock), Empty enclosure, stainless steel enclosure, Height: 300 mm, Width: 200 mm, Depth: 150 mm, Basic material: Stainless steel 1.4301 (304), Brushed, silver
Order No.	2470690000
Type	KEBI QL 302015 S2B0
GTIN (EAN)	4050118590326
Qty.	1 items
Delivery status	This article will no longer be available in the future.
Available until	2022-12-12T00:00:00+01:00

KEBI QL 302015 S2B0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals	
ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E243298

Dimensions and weights

Depth	150 mm	Depth (inches)	5.9055 inch
Height	300 mm	Height (inches)	11.811 inch
Width	200 mm	Width (inches)	7.874 inch
Diameter	9 mm	Mounting dimension - height	250 mm
Mounting dimension - width	150 mm	Wall thickness, min.	1.25 mm
Wall thickness, max.	1.25 mm	Net weight	3390 g

Temperatures

Operating temperature	-40 °C...85 °C	Operating temperature range	-40...85 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Cable glands, left

M63	2	M12	33
M50	3	M16	27
M32	5	M25	12
M20	14	M40	4

Cable glands, right

M25	12	M63	2
M16	27	M40	4
M50	3	M32	5
M20	14	M12	33

Cable glands, top/bottom

M20	8	M12	21
M63	1	M40	2
M32	3	M25	6
M50	2	M16	15

Certificate numbers enclosure

Declaration of Conformatiy No. (DoC LVD)	DE PS2650 180129 001ISS00	Approval conditions	cULus
Certificate no. (cULus)	E243298		

KEBI QL 302015 S2B0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

General information

Material thickness of cover	1.25 mm	Material thickness of enclosure	1.25 mm
Operating temperature, max.	85 °C	Operating temperature, min.	-40 °C
Lid attachment	Quarter-turn fastener with slotted insert	Standards	DIN EN 62208, IEC 60529
Surface finish	Brushed	Impact resistance	10.00 J
Protection degree	IP66	Basic material	Stainless steel 1.4301 (304)
Seal material	Polyurethane foamed	Integral fixing	Screwed
Enclosure attachment	Fixing lugs, Installation through the housing rear wall	Seal material of cover	Polyurethane foamed
Protection class (UL)	Type 3, Type 4X, Type 5	Access opening: width	142.5 mm
Opening angle lid	125.00 °	Flange plate	No
Lid	Yes	Access opening: height	242.5 mm
Areas of use	Harbour facilities, Machine construction, Transportation, Marine engineering, Packaging industry, Process industry		

Housing earth

Earth, enclosure, cover	Welded-on M6 stainless-steel earth stud in enclosure body and lid.	Earth, enclosure, external	M6 earth tab rivet
Earth, enclosure, internal	Welded-on M6 stainless-steel earth stud in enclosure body and lid.		

horizontal assembly

WDU 10 / ZDU 10	3x9	WDU 16 / ZDU 16	3x7
WDU 2,5 / ZDU 2,5 / IDU 2,5	3x17	WDU 35 / ZDU 35	3x5
WDU 4 / ZDU 4	3x14	WDU 6 / ZDU 6	3x11

vertical assembly

WDU 10 / ZDU 10	1x18	WDU 16 / ZDU 16	1x15
WDU 2,5 / ZDU 2,5 / IDU 2,5	1x36	WDU 35 / ZDU 35	1x11
WDU 4 / ZDU 4	1x30	WDU 6 / ZDU 6	1x23

Classifications

ETIM 6.0	EC000261	ETIM 7.0	EC000261
ETIM 8.0	EC000261	ETIM 9.0	EC000261
ETIM 10.0	EC000261	ECLASS 9.0	27-18-01-01
ECLASS 9.1	27-18-92-90	ECLASS 10.0	27-18-01-01
ECLASS 11.0	27-18-01-01	ECLASS 12.0	27-18-01-01
ECLASS 13.0	27-18-01-01	ECLASS 14.0	27-18-01-01
ECLASS 15.0	27-18-01-01		

KEBI QL 302015 S2B0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

